



The foundation of Blue Coat's application delivery infrastructure, Blue Coat ProxySG® appliances establish points of control that accelerate and secure business applications for users across the distributed organization. As the world's leading proxy appliance, the Blue Coat ProxySG is a powerful yet flexible tool for improving both application performance and security, removing the need for compromise.

FEATURES

Control — Proxy Services

Proxy support for multiple protocols

- > HTTP, CIFS, SSL, FTP, MAPI, P2P, MMS, RTSP, QuickTime, TCP-Tunnel, DNS, SOCKS, IM
- > Bandwidth management on all proxy services
- > SSL Termination & Proxy (forward and reverse)
- > Control encrypted traffic for all users and applications inside & outside the enterprise

Content Filtering and Security

- > WebFilter continuously updated by WebPulse cloud service for malware detection and content ratings
- > On-proxy support of leading URL lists, popular regional lists, custom lists, or custom categories
- > Strip and replace Web content, plus IM file sharing controls
- > Log and block P2P traffic

Inline Malware Detection

- > ProxyAV integration with ProxySG
- > Choice of anti-malware engines

IM Controls and Logging

- > MSN, Yahoo!, AOL Messengers
- > Method level control settings

Streaming Controls

- > Flash, MS, Real, QuickTime
- > Stream splitting & caching

ProxyClient

- > Remote Filtering with WebPulse cloud service
- > Remote Acceleration for file and application performance

Performance & Reliability — SGOS

Platform highlights:

- > Secure object-based operating system with small footprint
- > High-speed caching with advanced object pipelining and adaptive refresh
- > Built-in pass-through network card, compression services, bandwidth management, and SSL off loading

Network functionality including:

- > Active/Active bridging support using virtual IP addressing for failover and remote installations

- > Routing configurations for gateway, route tables, RIP, DNS, and WCCP
- > Health checks performed on a forwarding host or external servers to verify status and availability of device
- > 19" Rack mountable (with kit) or portable use Integrated support services
- > View & submit service requests via the Blue Coat management interface
- > Send snapshots (trace files) to Blue Coat Support Services for faster resolution

Manageability — Policy Processing Engine

Authentication

- > Utilize a company's existing authentication source for integrated SSO, including local password files, NTLM, LDAP (Active Directory, eDirectory, SunOne), CA eTrust SiteMinder, Microsoft Kerberos, Oracle Access Manager, RADIUS and certificates
- > Multi-realm authentication sequencing
- > Forms-based authentication support

Powerful management interface

- > Web-based management interface
- > Optional command line interface
- > Alerting via SNMP, SMTP and logging administrative events

Comprehensive policy definitions

- > Graphical Visual Policy Manager with layered policy definitions
- > Definable triggers and actions for policy definition

Content Policy Language (CPL)

- > Create custom text-based policies to address unique policy requirements
- > Built-in text editor for CPL allows sample code to be copied and pasted from Blue Coat TechBriefs or Support Services advisories

Extended Management with Director

- > Distribute, backup, restore policy files for multiple Blue Coat ProxySG appliances
- > Manage policy by device, group, or region
- > Job scheduling/job status reporting

Management & Control of ProxyClients

- > Configure, provision and maintain global deployment of ProxyClients
- > Accelerate applications by user
- > Centralized policy management and reporting for Remote Filtering

Visibility — Management Reporting

Default logging

- > HTTP, HTTPS, CIFS, MAPI, FTP, TCP-Tunnel, P2P, IM, Windows Media, Real Media, QuickTime, DNS, SOCKS
- > Global log file limits and upload sizing
- > Client upload settings and scheduling

Custom logging and trace files

- > Selectable fields/text/log formats

Statistics

- > Bandwidth Gain
- > HTTP/HTTPS/FTP history
- > Streaming history
- > Resources

SNMP Support

- > Trap settings, community strings

Aggregate Blue Coat ProxySG Logs with Reporter

- > Reporter Dashboard™ provides a "drill-able" overview of Web activity
- > 150+ pre-defined reports track user activity, security risks, and Web traffic performance
- > Secure browser access/role-based viewing
- > Provides real-time reporting with continuous log uploads

Acceleration — MACH5

Bandwidth Management

- > Assign priority and network resources based on port, device, applications or content to reflect corporate policies

Protocol Optimization

- > Improve inefficient protocols by making them more tolerant to higher latencies

Byte Caching

- > Cache repetitive traffic found in the byte stream and serve it locally to reduce WAN traffic

Object Caching

- > Store files, videos and Web content locally, providing LAN-like performance over WAN

Compression

- > Inline compression can reduce predictable patterns even on the first pass



SG210 SERIES	SG210-5	SG210-10	210-25	Physical Properties	
License Capacity - Concurrent Users				Dimensions and Weight	
With ADN Enabled	10	50	Unlimited		Enclosure
Without ADN Enabled	30	150	Unlimited	Dimensions (L x W x H)	35.6cm x 19.1cm x 4.4cm (14in x 7.5in x 1.72in)
System				Weight (maximum)	2.6kg(5.8lb)
Disk drives	1x80GB IDE	137GB IDE accessible (250GB IDE model)	137GB IDE accessible (250GB IDE model)	Operating Environment	
RAM	512MB	1GB	1GB	Power	AC power 100-240V, 50-60Hz, 6.3-3.0A
Network Interfaces	(2) integrated (on board) 10/100Base-T NICs with passthrough	(2) integrated (on board) 10/100Base-T NICs with passthrough SSL Offload Card	10/100Base-T NICs with passthrough	Maximum Power	45 Watts
Optional NICs/Cards	SSL Offload Card	None	None	Thermal Rating	153.63 BTU/Hr
				Temperature	5°C to 35°C (41°F to 95°F)
				Humidity	Less than 90% relative humidity, non-condensing
				Altitude	Up to 3048 M (10,000 ft)

SG510 SERIES	SG510-5	SG510-10	SG510-20	SG510-25	Physical Properties	
License Capacity - Concurrent Users					Dimensions and Weight	
With ADN Enabled	50	125	300	Unlimited		Enclosure
Without ADN Enabled	200	500	1200	Unlimited	Dimensions (L x W x H)	58cm x 44cm x 4.4cm (22.8in x 17.4in x 1.7in)
System					Weight (maximum)	12.3kg(27lb) 12.7kg(28lb) 12.7kg(28lb) 12.7kg(28lb)
Disk drives	2x80GB SATA	2x320GB SATA	2x320GB SATA	2x320GB SATA	Operating Environment	
RAM	2GB RAM	2GB RAM	2GB RAM	2GB RAM	Power	AC power 100-240V, 50-60Hz, 6.3-3.0A
Network Interfaces	(2) integrated (on board) 10/100/1000 Base-T NICs	(2) integrated (on board) 10/100/1000 Base-T NICs	10/100/1000 Base-T NICs	10/100/1000 Base-T NICs	Maximum Power	150 Watts
Optional Cards	SSL Offload card	None			Thermal Rating	512 BTU/Hr
Optional NICs	2x10/100/1000Base-T card (dual GigE)	2x10/100/1000Base-T card (dual GigE)	2x10/100/1000Base-SX card (dual GigE Fibre)	4x10/100/1000Base-T card (quad GigE with passthru)	Temperature	5°C to 35°C (41°F to 95°F)
					Humidity	Less than 90% relative humidity, non-condensing
					Altitude	Up to 3048m (10,000ft)

SG810 SERIES	SG810-5	SG810-10	SG810-20	SG810-25	Physical Properties	
License Capacity - Concurrent Users					Dimensions and Weight	
With ADN Enabled	500	700	1000	Unlimited		Enclosure
Without ADN Enabled	2500	3500	5000	Unlimited	Dimensions (L x W x H)	58cm x 44cm x 4.4cm (22.8in x 17.4in x 1.7in)
System					Weight (maximum)	14.1kg(31lb) 14.5kg(32lb) 15.4kg(34lb) 15.4kg(34lb)
Disk drives	2x73GB SCSI Ultra 320	2x300GB SCSI Ultra 320	4x300GB SCSI Ultra 320	4x300GB SCSI Ultra 320	Operating Environment	
RAM	2GB RAM	4GB RAM	6GB RAM	6GB RAM	Power	AC power 100-240V, 50-60Hz, 6.3-3.0A
Network Interfaces	(2) integrated (on board) 10/100/1000 Base-T NICs	(2) integrated (on board) 10/100/1000 Base-T NICs	10/100/1000 Base-T NICs	10/100/1000 Base-T NICs	Maximum Power	375 Watts
Optional Cards	SSL Offload card	None			Thermal Rating	1280.25 BTU/Hr
Optional NICs	2x10/100/1000Base-T card (dual GigE)	2x10/100/1000Base-T card (dual GigE)	2x10/100/1000Base-SX card (dual GigE Fibre)	4x10/100/1000Base-T card (quad GigE with passthru)	Temperature	5°C to 35°C (41°F to 95°F)
					Humidity	Less than 90% relative humidity, non-condensing
					Altitude	Up to 3048m (10,000ft)

SG8100 SERIES	SG8100-5	SG8100-10	SG8100-20	Physical Properties	
License Capacity - Concurrent Users				Dimensions and Weight	
With/Without ADN Enabled	Unlimited	Unlimited	Unlimited		Enclosure
System				Dimensions (L x W x H)	59.2cm X 44.2cm X 17.652cm (23.3in X 17.4in X 6.95in)
Disk drives	2x300GB SCSI Ultra 320	4x300GB SCSI Ultra 320	8x300GB SCSI Ultra 320	Weight (maximum)	25.4kg(56lb) 27.2kg(60lb) 30.8kg(68lb)
RAM	4GB RAM	6GB RAM	8GB RAM	Operating Environment	
Network Interfaces	(2) integrated (on board) 10/100/1000 Base-T NICs	(2) integrated (on board) 10/100/1000 Base-T NICs	10/100/1000 Base-T NICs	Power	AC power 100-240V, 50-60Hz, 6.3-3.0A
Optional Cards	SSL Offload card - only available for 8100-5			Maximum Power	525 Watts
Optional NICs	2x10/100/1000Base-T card (dual GigE)	4x10/100/1000Base-T card (quad GigE with passthru)	4x10/100/1000Base-SX card (quad GigE Fibre)	Thermal Rating	1792 BTU/Hr
				Temperature	5°C to +40°C (41°F to 104°F)
				Humidity	Less than 90% relative humidity, non-condensing
				Altitude	Up to 3000 M (9,483 ft)
				DC Adapter Voltage	36-72 volts DC Steady state current: 28 amp (typical) Inrush current: less than 10 amps (per module)

FOR ALL PROXYSG SERIES

Regulations	
Emissions	FCC Class A, EN55022 Class A, VCCI Class A No.1706609, BSMI, CCC, C-tick
Safety	CSA C22.2 No. 950 M95, UL 60950 3rd Edition, EN60950, TUV-GS, TUV-S, CCC, BSMI
Standards	UL/CSA, TUV-S, BSMI, C-tick, CCC, CE
Support Standard Warranty	90-day software & phone support with 1-year hardware support; extended and upgraded support plans available

Blue Coat Systems, Inc. 1.866.30.BCOAT // +1.408.220.2200 Direct • +1.408.220.2250 Fax • www.bluecoat.com

Copyright © 2008 Blue Coat Systems, Inc. All rights reserved worldwide. No part of this document may be reproduced by any means nor translated to any electronic medium without the written consent of Blue Coat Systems, Inc. Specifications are subject to change without notice. Information contained in this document is

believed to be accurate and reliable, however, Blue Coat Systems, Inc. assumes no responsibility for its use. Blue Coat is a registered trademark of Blue Coat Systems, Inc. in the U.S. and worldwide. All other trademarks mentioned in this document are the property of their respective owners. v.DS-SGOS-v2.1 - 1008